IN THE SPECIFICATION

Please, enter the Substitute Specification enclosed. The Substitute Specification does not contain any new matter, it merely corrects the deficiencies the Examiner has pointed out in the outstanding and in the previous Office Actions.

SUBSTITUTE SPECIFICATION

Patent Application of

Marvin Byrd

For

TITLE: COMPANION RIDER WHEEL CHAIR

BACKGROUND & CROSS REFERENCES TO RELATED APPLICATIONS

This application is entitled to benefit of Provisional Patent Application Serial Number 60/263,496 filed on January 23, 2001.

FEDERALLY SPONSORED RESEARCH

The invention that is the subject matter of the present application was not a recipient of any federal support for its research and development.

REFERENCE TO MICROFICHE APPLICATION

Not applicable

BACKGROUND OF THE INVENTION

This invention relates to the field of wheel chair devices that are used by the physically challenged for movement and convenience.

Most wheelchairs that are found in the market are custom made to fit a particular person, with specific height and width dimensioned to suit the physical configuration of the future user of the wheelchair. Furthermore, wheelchairs found in the prior art are relatively bulky and heavy and are not easy to store because of their complicated configuration, such as the cooperative escalator and wheel chair of Patent No. 4,326,622 (Ellzey, 1982). With respect to wheelchairs with seats are divided, Patent No. 5,405,187 (Söderlund, 1995) describes a wheelchair where the seat is divided longitudinally. With respect to motorized wheelchair devices, they are present in the prior art, such as the motorized invalid chair transport vehicle claimed in Patent No. D320,579 (Manning et al, 1991), and in the universal electric wheeled chair described in Patent No. 4,941,540 (Bernstein, 1990). Nevertheless, no prior art neither of lighter wheelchairs -such as the universal wheeled chair claimed in Patent 4,825,971 (Bernstein, 1989)- or of motorized wheelchair describe the use of a coupling devise to allow a standard wheelchair to be coupled to a motorized devise.

With respect to devices to hold the two members together when used as companion rider wheelchair, there are locks in the prior art such as the self locking, rattle resistant fork bolt described in Patent No. 6,022,166 (Rogers et al, 2000), but do not claim nor disclose the system used in the present invention.

BRIEF SUMMARY OF THE INVENTION

This invention constitutes a lightweight wheeled chair forming a companion rider device formed of hollow tubular frame members. The seat is preferably cantilevered from

rear frame members. The frame includes two lower side frame members having back wheels mounted at the rear ends and smaller castor wheels mountable to the front end In one embodiment the front end of the two lower side members are coupled together using two coupling frame members inter-coupling the upper side and lower side frame members to permit adjustment and collapsing of the wheeled chair. Two upper side members extend forwardly from the rear of the wheeled chair, and are secured to the rear frame members. A seat may be supported directly on these two upper side frame members, or the two upper side frame members may serve as arms for the wheeled chair, with the seat being slung from these arms at a lower position. The present invention is to provide a lightweight wheelchair that can be used as a standalone wheelchair, as well as for a recreational use coupled to a motorized vehicle.

Advantages of the new wheelchair include the fact that it is very lightweight, with the estimate of its weight being approximately 18 pounds. An additional advantage, of course, is the fact that it may be readily adjusted in height, from kitchen counter-top level to a much lower desk height level. The unit can be constructed to be foldable so that it may easily fit into the back seat or trunk of a car.

In view of the foregoing, various objects of the present invention include the following:

1. One object of the present invention is to provide a lightweight wheelchair that can be

used as a standalone wheelchair, as well as for a recreational use coupled to a motorized vehicle, such as a motorized wheel chair.

2. Another object of the present invention is to provide a wheelchair in which the width of the wheelchair between the side arms may be readily varied, and wherein the height of the seat of the wheelchair may be easily changed.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be more clearly understood after reference to the following detailed description of the preferred embodiment read in conjunction with the drawings, wherein:

Fig. 1. is a photograph side elevation view of a wheelchair illustrating an early embodiment of the present invention.

Fig. 2 A Illustrates a perspective view of the adjustable wheel chair with the towing bar device attached to it.

Fig. 2 B Illustrates a perspective view of the adjustable wheel chair with the castor wheel assemblies attached to it.

Fig. 3 is a sectional view of the adjustable companion rider wheel chair frame and the attachable towing device.

Fig. 3A illustrates the adjustable chair frame and the towing bar attachment.

Fig. 3B illustrates the coupling system of the motorized vehicle for pin coupling of the tow bar.

Fig. 3C illustrates the towing bar.

Fig. 3D illustrates the castors.

Fig. 4. illustrates an alternative embodiment of the wheelchair frame.

Fig. 5. is a photograph of the invention reduced to practice.

DETAILED DESCRIPTION OF THE INVENTION

In accordance with one aspect of the present invention, a lightweight companion rider wheel chair, a frame having two lower side frame members **30**, with wheels **42** mounted at front end **31** and at rear end **32** thereof, and two rear frame members **33** , with the lower ends**34** of each of the rear frame members **33** being secured to the rear ends **32** of the lower side frame members **30**. In addition, two forwardly extending upper side members **35** are provided, with these upper side frame members **35** being mechanically secured to the upper ends **36** of the two rear frame members **33**. With regard to the arms and seat of the wheeled chair, they may be arranged in one of two alternative ways. As one alternative, the forwardly extending upper side members **35** may be the wheelchair

arms, and the seat may be supported by a sling from these arms. As another alternative, another set of forwardly extending upper frame members **37** may be provided, with this set constituting the arms of the wheeled chair, and the forwardly extending upper side members **35** constituting the support for the seat. (See Figures 2 A, B and 4). One feature of the invention is that arrangements maybe provided for changing the spacing of the side members, thereby causing the "X" configuration **38** to pivot about their central pivot point and have the arms of the wheelchair come closer or farther apart, and correspondingly raise and lower the height of the seat.

The height of the chair can be adjusted by adjusting the attachment of the castor wheels **40** and the rear wheels **42**. The castors **39** are attachable to the front end **31** of the lower side frame **30** with a coupling mechanism **4, 5**. The castor wheels **40** can be attached in any of the several holes **8** provided in the castor wheel attachment **41**. The rear wheels **42** can be attached into any of the several holes **6** provided in the lower end **34** of the rear frames **33.**

The rear wheels **42** can furthermore be adjusted depending of the weight of the person sitting in the chair by attaching the back wheels **42,** into any of the several holes **7** provided in the rear end **32** of the lower side frames **30.**

In order to use the wheel chair as a companion rider, the castor assemblies **39** are removed and instead a tow bar attachment **1** is attached in the front ends **31** of the lower side frames **30**. Alternatively, the tow bar attachment is permanently fixed to the front

ends of the lower side frames **30** (see Fig. 4). The rear end **45** of a tow bar **2** is attached to the tow bar attachment **1** with a pin-coupling coupler **46**. The tow bar **2** is curved downwardly and the lowest part of the bar forms a rest for the feet **43**. The front end **44** of the tow bar **2** is coupled to a coupling mechanism **3** in the motorized vehicle with another pin-coupling coupler **47.**

Other features of the invention may involve one or more of the following:

1. The front ends **31** of the lower side members **30** may be coupled together with a combination of frame members and linear bearings, to maintain alignment of the lower side frame members.

2. Advantages of the new wheelchair include the fact that it is very lightweight, with the estimate of its weight being approximately 18 pounds.

3. An additional advantage, of course, is the fact that it may be readily adjusted in height, from kitchen counter-top level to a much lower desk height level. The unit may be collapsable so that it may easily fit into the back seat or trunk of a car.

The invention is operated by coupling the wheelchair device to a motorized vehicle such as an electric wheelchair or golf cart by means of the pin-coupling device. The rider then can be pulled along for recreational purposes by the motorized vehicle.

The invention can be used as a standalone wheelchair, or as a coupled device to a motorized devise. The wheelchair invention described here is also available as a

collapsible device so it can be stored and carried easily and conveniently, such as in the trunk of a car. The alternative embodiments described here are examples only; the scope of the invention shall be as described within the claims of the invention.

This device offers a unique device for transport and recreation of those persons requiring the use of a wheelchair for movement. It improves the quality of life of the physically challenged and allows for more mobility in the community at large. The scope of the invention described here is for example only. The scope of the invention shall be determined as described within the claims of the invention.

SEQUENCE LISTING

Not applicable

ABSTRACT

This invention constitutes a lightweight wheeled chair forming a companion rider device formed of hollow tubular frame members. A tow bar can be attached to the tow bar attachment with a pin coupling assembly. The tow bar attachment is mountable to the front ends of the lower side frame of the chair or it may also be permanently fixed there. The tow bar is downwardly curved from its middle and it has a feet rest. The height of the wheelchair may be adjusted by mounting the back wheels and the castor wheels in different adjusting holes provided in the chair frames and in castor wheel attachement. The present invention is to provide a lightweight wheelchair that can be used as a standalone wheelchair, as well as for a recreational use coupled to a motorized vehicle, such as an electric wheelchair.